

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)						
		SW	OD					Speed, km/h (mph)					Tractor application	
		mm/in	mm/in					Static	10	30	40	50	65	
									6	19	25	31	40	
560/ 45 R 22.5 FT	AG16.00	543 21.4	1076 42.4	493 19.4	3279 129.1	152D 152D	0.8	3200	2500	2100	1890	1680	1390	
							12	7050	5510	4630	4160	3700	3060	
							1.6	4780	3740	3140	2830	2520	2080	
							23	10530	8240	6920	6230	5550	4580	
							2.4	6070	4750	3990	3590	3190	2640	
							35	13370	10460	8790	7910	7030	5810	
							3.2	7180	5620	4710	4240	3780	3120	
							46	15810	12380	10370	9340	8330	6870	
							3.6	7680	6010	5040	4540	4040	3340	
							52	16920	13240	11100	10000	8900	7360	
							4	8170	6390	5360	4830	4300	3550	
							58	18000	14070	11810	10640	9470	7820	

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards