

# TORQUEMAX



**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life

**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction


**FEATURE**

- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage

## MACHINERY



### High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF710/ 60R38 NRO	DW24B DW25B DW27B	710 28.0	1820 71.7	799 31.5	5375 211.6	171D	0.8	9430	4390	4100	4100	3730	1.6	5740	
							12	20770	9670	9030	9030	8220	23	12640	
							1	10740	5000	4670	4670	4250	1.8	6540	
							15	23660	11010	10290	10290	9360	26	14410	
							1.2	11960	5570	5200	5200	4730	2	7280	
							17	26340	12270	11450	11450	10420	29	16040	
							1.4	13090	6100	5690	5690	5180	2.2	7970	
							20	28830	13440	12530	12530	11410	32	17560	
							1.6	14150	6590	6150	6150	5600	2.4	8610	
23	31170	14520	13550	13550	12330	35	18960								

\* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards