

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
		mm/in	mm/in					static	10	20	25 to 65	70	bar	30	
IF710/ 70R38 CFO	DW23B DW25B	720 28.3	1959 77.1	850 33.5	5800 228.3	178D	0.8	9060	4930	4040	3940	3590	1.6	5520	
							12	19960	10860	8900	8680	7910	23	12160	
							1.2	11500	6250	5130	5000	4550	2	7000	
							17	25330	13770	11300	11010	10020	29	15420	
							1.6	13620	7400	6070	5920	5390	2.4	8290	
							23	30000	16300	13370	13040	11870	35	18260	
							2.8	18880	10260	8420	8210	7470	3.6	11490	
							41	41590	22600	18550	18080	16450	52	25310	
							2.4	17250	9380	7690	7500	6830	3.2	10500	
35	38000	20660	16940	16520	15040	46	23130								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards