

# FARMAX HPT



**FEATURE**

Lug Tip Step

**BENEFIT**

Increase the grip and reducing the tractor slip

**FEATURE**

Extra wide tread

**BENEFIT**

Wider footprint provides increased stability

**FEATURE**

Rounder shoulder

**BENEFIT**

Provides less soil damage  
Better Grip

**FEATURE**

Lug base tie bar

**BENEFIT**

Additional support to lugs and also helps to remove mud from lugs

**FEATURE**

50° lug angle at centre

**BENEFIT**

Smoother road driving comfort, less noise and vibration


**FEATURE**

Deeper Tread Depths

**BENEFIT**

Provides improved traction and gripping power longer tire life

## MACHINERY



### High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)																																																																																										
		SW	OD					Speed, km/h (mph)																																																																																										
								Tractor application																																																																																										
		mm/in	mm/in					mm/in	mm/in	mm/in	mm/in	Static	10	20	30	40	50	65																																																																																
600/70R30	DW18L	610	1602	726	4781	168D/171A8	0.8	5130	3350	2740	2560	2440	2340	2230																																																																																				
															DW20L	24.0	63.1	28.6	188.2	12	11300	7380	6040	5640	5370	5150	4910																																																																							
	1.2																											6510	4250	3480	3250	3100	2970	2830																																																																
																																			17	14340	9360	7670	7160	6830	6540	6230																																																								
																																											1.8	8260	5390	4420	4130	3930	3770	3590																																																
																																																			26	18190	11870	9740	9100	8660	8300	7910																																								
																																																											2	8790	5730	4700	4390	4180	4010	3820																																
																																																																			29	19360	12620	10350	9670	9210	8830	8410																								
																																																																											2.4	9780	6380	5230	4890	4650	4460	4250																
																																																																																			35	21540	14050	11520	10770	10240	9820	9360								
																																																																																											3.8	12880	8400	6890	6440	6130	5880	5600

All tires confirms ETRTO T&RA & STRO standards