

FARMAX R70

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- · Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

• Dual lug angle

- Better Roadability

FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder


BENEFIT

· Less soil disturbance

BENEFITS

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Туре	Rlm	Unloaded Dimension					Speed kmph /mph					
				sw	OD	SLR	RC	Infl.Press	Static	10	20	30	40	50
										6	12	19	25	31
				mm	mm	mm	mm	bar		Recommend load kg /lbs				
				in	in	in	in	psi		11000111110110 Todd kg / IDS				
320/70R20	123 A8/B	H	W9 W10 W11	320 12.6	982 38.7	446 17.6	2909 114.5	1.3	2480	1620	1330	1160	1080	1080
								19	5460	3570	2930	2560	2380	2380
								1.6	2810	1830	1500	1310	1220	1220
								23	6190	4030	3300	2890	2690	2690
								2	3200	2090	1710	1490	1390	1390
								29	7050	4600	3770	3280	3060	3060
								2.4	3570	2330	1910	1660	1550	1550
								35	7860	5130	4210	3660	3410	3410

All tires confirms ETRTO T&RA & STRO standards