

# FLOTATION T422



**FEATURE**

- Tough nylon casing
- Strong brad buldle

**BENEFIT**

- High load carrying capacity

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced damage to crops


**FEATURE**

- Larger volume and footprint

**BENEFIT**

- Reduced compaction

## MACHINERY



Trailer

| Size        | Load Index/<br>Speed Index<br>(Free Rolling) &<br>(Drive Wheel) | PR | Type | Rim       | Unloaded dimension |      | SLR  | RC    | Infl. Press | Load carrying capacity |             |     |     |
|-------------|---|----|------|-----------|--------------------|------|------|-------|-------------|------------------------|-------------|-----|-----|
|             |   |    |      |           | SW                 | OD   |      |       |             | Free Rolling           | Drive Wheel |     |     |
|             |   |    |      |           | mm                 | mm   |      |       |             |                        |             | kg  | kg  |
|             |   |    |      |           | in                 | in   |      |       |             |                        |             | lbs | lbs |
| 550/45-22.5 | 171 A8/ 167 B (FR)<br>&<br>158 A8 / 154B (DW)                   | 20 | TL   | 16.00 DCx | 550                | 1238 | 540  | 3720  | 3.5         | 6150                   | 4250        |     |     |
|             |   |    |      | 22.5      | 21.6               | 48.7 | 21.2 | 146.4 | 51          | 13560                  | 9370        |     |     |

Also available in sizes: 500/60-22.5, 550/45-22.5, 550/60-22.5, 600/50-22.5, 600/55-22.5, 700/40-22.5, 700/50-22.5, 600/55-26.5, 700/50-26.5, 800/45-26.5

All tires confirms ETRTO T&RA & STRO standards