

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)					
		SW	OD	Radius				Speed, km/h (mph)					
		mm	mm	mm	mm	Speed	bar	MIXED APPLICATION					
		in	in	in	in	Symbol	psi	Static	10	30	40	50	65
								6	19	25	31	40	
580 65R22.5 FT	AG16.00	577 22.7	1318 51.9	601 23.7	3996 157.3	166D 166D	0.8	4760	3730	3130	2820	2500	2070
							12	10480	8220	6890	6210	5510	4560
							1.6	7130	5580	4680	4220	3750	3100
							23	15700	12290	10310	9300	8260	6830
							2.4	9040	7070	5930	5340	4760	3930
							35	19910	15570	13060	11760	10480	8660
							3.2	10700	8370	7020	6320	5630	4650
							46	23570	18440	15460	13920	12400	10240
							4	12190	9540	8000	7210	6410	5300
58	26850	21010	17620	15880	14120	11670							

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards