FARMAX R85



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc \bigcirc • Wider tread BENEFITS

Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		ei D	RC	Infl. Press	Speed kmph /mph					
				SW	OD	SLR	ΠŪ	IIII. Fress	Static	10	20	30	40	50
									otatic	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	neconiniena ioaa ky / ios					
520/85R42	157 A8/B	TL						0.8	6330	4130	3380	2940	2750	2750
								12	13940	9100	7440	6480	6060	6060
							1	7200	4700	3850	3350	3130	3130	
			DW16L	530	1951 76.8	889 35	5791 228	15	15860	10350	8480	7380	6890	6890
			DW18L	20.9				1.3	8400	5480	4490	3910	3650	3650
								19	18500	12070	9890	8610	8040	8040
								1.6	9490	6190	5070	4410	4125	4125
								23	20900	13630	11170	9710	9090	9090

Reduced soil compactionIncreased footprint

All tires confirms ETRTO T&RA & STRO standards