FARMAX R85



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc \bigcirc • Wider tread BENEFITS

Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	δLN	nu	IIII. Fress	Static	10	20	30	40	50
									Static	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	neconinienu Ioau ky / Ios					
460/85R34	157 A8/B	TL	W16L W15L W14L	480 18.9	1646 64.8	752 29.6	4895 192.7	2	7480	4880	4000	3480	3250	3250
								29	16480	10750	8810	7670	7160	7160
								2.3	8120	5300	4340	3780	3530	3530
								33	17890	11670	9560	8330	7780	7780
								2.6	8720	5690	4660	4060	3790	3790
								38	19210	12530	10260	8940	8350	8350
								3	9490	6190	5070	4410	4125	4125
								44	20900	13630	11170	9710	9090	9090

Reduced soil compactionIncreased footprint

All tires confirms ETRTO T&RA & STRO standards