

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
600/65R38	153D	TL	DW20B W18L	600 23.6	1745 68.7	798 31.4	5236 206.2	0.8	2790	2880	2660	2550	2430	1	4130	3770
								12	6150	6340	5860	5620	5350	15	9100	8300
								1	3190	3280	3030	2910	2770	1.25	4710	4290
								15	7030	7220	6670	6410	6100	18	10370	9450
								1.3	3710	3830	3540	3390	3230	263	5490	5010
								19	8170	8440	7800	7470	7110	3811	12090	11040
								1.6	4200	4330	4000	3830	3650	2	6210	5660
								23	9250	9540	8810	8440	8040	29	13680	12470