

# FARMAX R65

**FEATURES**

- Greater lug overlap
- More lugs in footprint

**BENEFITS**

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

**FEATURES**

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

**BENEFITS**

- Better self cleaning properties
- Less soil from field to road



**FEATURE**

- R1-W tread depth

**BENEFIT**

- Long service life

**FEATURES**

- Lower lug angle at shoulder
- Higher lug angle at centre

**BENEFITS**

- Better traction
- Better ride

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced soil disturbance


**FEATURE**

- Wider tread

**BENEFITS**

- Lower soil compaction
- Increased footprint area

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
540/65R38	153D	TL	W16L W18L	550 21.7	1667 65.6	767 30	4975 196	1.8	3540	3650	3370	3230	3080	2.25	5240	4770
								26	7800	8040	7420	7110	6780	33	11540	10510
								2	3770	3890	3590	3440	3280	2.5	5580	5080
								29	8300	8570	7910	7580	7220	36	12290	11190
								2.2	3990	4110	3800	3640	3470	2.8	5900	5380
								32	8790	9050	8370	8020	7640	40	13000	11850
								2.4	4200	4330	4000	3830	3650	3	6210	5660
								35	9250	9540	8810	8440	8040	44	13680	12470

All tires confirms ETRTO T&RA & STRO standards