

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
600/65R34	151 D	TL	DW20B W18L	600 23.6	1644 64.7	748 29.4	4916 193.5	0.8	2650	2730	2520	2420	2300	1	3910	3570
								12	5840	6010	5550	5330	5070	15	8610	7860
								1	3010	3100	2870	2750	2620	1.3	4450	4060
								15	6630	6830	6320	6060	5770	18	9800	8940
								1.3	3520	3630	3350	3210	3060	1.6	5200	4740
								19	7750	8000	7380	7070	6740	24	11450	10440
								1.6	3970	4090	3780	3620	3450	2	5870	5350
								23	8740	9010	8330	7970	7600	29	12930	11780