

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
440/65R24	128D	TL	W13L W14L W15L	441 17.4	1182 46.5	540 21	3501 137.8	0.8	1370	1410	1300	1250	1190	1	2020	1840
								12	3020	3110	2860	2750	2620	15	4450	4050
								1	1560	1610	1490	1430	1360	1.25	2310	2110
								15	3440	3550	3280	3150	3000	18	5090	4650
								1.3	1830	1880	1740	1670	1590	263	2700	2460
								19	4030	4140	3830	3680	3500	3811	5950	5420
								1.6	2070	2130	1970	1890	1800	2	3060	2790
								23	4560	4690	4340	4160	3960	29	6740	6150