RPG

FARMAX R85

CEAT SPECIALTY

FEATURE
- Higher angle and lug overlap at centre

BENEFIT
- Better roadability

FEATURE
- R1-W tread depth

BENEFIT
- Longer tyre life

FEATURE
- Wider tread
- Larger inner volume

BENEFIT
- Reduced soil compaction

FEATURE
- Rounded shoulder

BENEFIT
- Reduced damage to soil and crop

FEATURE
- Lower angle at shoulder

BENEFIT
- Superior traction

MACHINERY



Tractor

Size	Rim	Infl tire dimension SW mm in	Infl tire dimension OD mm in	Static Loaded radius mm in	Rolling circm. mm in	Load Index Speed Symbol	Infl. press. bar psi	Recommended load, kg (lbs) Static	Speed, km/h (mph) 10 / 6	20 / 12	30 / 19	40 / 25	50 / 31
520/ 85R38	DW16L DW18L	530 20.9	1855 73.0	847 33.3	5513 217.1	155 A8 155 B	0.8	5930	3870	3170	2760	2580	2580
							12	13060	8520	6980	6080	5680	5680
							1.0	6760	4410	3620	3150	2940	2940
							15	14890	9710	7970	6940	6480	6480
							1.3	7890	5150	4220	3670	3430	3430
							19	17380	11340	9300	8080	7560	7560
							1.6	8910	5810	4770	4150	3875	3875
							23	19630	12800	10510	9140	8540	8540

All tires confirms ETRTO T&RA & STRO standards