

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
									Recommend load kg /lbs					
360/70R20	120 A8/B	TL	W12 W11 W10	360 14.2	1042 41	470 18.5	3075 121	0.8	2140	1400	1140	1000	930	930
								12	4710	3080	2510	2200	2050	2050
								1	2440	1590	1300	1130	1060	1060
								15	5370	3500	2860	2490	2330	2330
								1.3	2850	1860	1530	1330	1240	1240
								19	6280	4100	3370	2930	2730	2730
								1.6	3220	2100	1720	1500	1400	1400
								23	7090	4630	3790	3300	3080	3080

All tires confirms ETRTO T&RA & STRO standards