

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, km/h (mph)						
			SW	OD				Field	10	25	30	40	50	65
			mm/in	mm/in					mm/in	mm/in	bar	maximum Load, kg (lbs)		
270/95R42 (11.2R42)	139D/142A8	W9 W8 W10	275 10.8	1581 62.2	740 29.1	4793 188.7	2.8	2290	2990	2360	2180	2090	1990	1810
							41	5040	6590	5200	4800	4600	4380	3990
							3.2	2470	3230	2550	2350	2260	2150	1960
							46	5440	7110	5620	5180	4980	4740	4320
							3.6	2650	3450	2730	2520	2420	2300	2090
							52	5840	7600	6010	5550	5330	5070	4600
							4	2790	3650	2880	2660	2550	2430	2210
							58	6150	8040	6340	5860	5620	5350	4870