

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
320/70R20	113 A8/B	TL	W9 W10 W11	320 12.6	982 38.7	446 17.6	2909 114.5	bar psi	Recommend load kg /lbs					
								0.8	1770	1160	950	820	770	770
								12	3900	2560	2090	1810	1700	1700
								1	2000	1310	1070	930	870	870
								15	4410	2890	2360	2050	1920	1920
								1.3	2350	1530	1250	1090	1020	1020
								19	5180	3370	2750	2400	2250	2250
								1.6	2650	1730	1410	1230	1150	1150
								23	5840	3810	3110	2710	2530	2530