

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in				Recommend load kg / lbs						
270/95R48 (11.2R48)	142D/ 145A8	TL	W8 W9 W10	275 10.8	1733 68.2	816 32.1	5281 207.9	2.4	2390	3120	2460	2280	2180	2080	-
								35	5260	6870	5420	5020	4800	4580	-
								2.8	2620	3420	2700	2500	2390	2280	-
								41	5770	7530	5950	5510	5260	5020	-
								3.2	2840	3710	2930	2700	2590	2470	-
								46	6260	8170	6450	5950	5700	5440	-
								3.6	3050	3980	3140	2900	2780	2650	-
								52	6720	8770	6920	6390	6120	5840	-