

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in				Recommend load kg / lbs						
270/95R38 (11.2R38)	137D/ 140A8	TL	W8 W9 W10	275	1479	689	4507	2.8	2140	2790	2200	2040	1950	1860	1690
								41	4710	6150	4850	4490	4300	4100	3720
								3.6	2480	3240	2560	2370	2270	2160	1970
								52	5460	7140	5640	5220	5000	4760	4340
								4	2650	3450	2730	2520	2420	2300	2090
								58	5840	7600	6010	5550	5330	5070	4600