

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, kmph (mph)						
				SW	OD				Field	10	25	40	50	65	70
				mm/in	mm/in					6	16	25	31	40	50
												Recommend load kg /lbs			
320/80R42 (12.4R42)	141A8/B	TL	W10	320 12.6	1580 62.2	744 29.3	4688 184.6	1.2	3340	2180	1780	1550	1450	-	-
								17	7360	4800	3920	3410	3190	-	-
								1.6	3960	2580	2120	1840	1720	-	-
								23	8720	5680	4670	4050	3790	-	-
								2.4	5010	3270	2680	2330	2180	-	-
								35	11040	7200	5900	5130	4800	-	-
3.2	5920	3860	3170	2760	2575	-	-								
46	13040	8500	6980	6080	5670	-	-								

All tires confirms ETRTO T&RA & STRO standards