

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in					Recommend load kg / lbs					
270/95R46 (11.2R46)	141D/ 144A8	TL	W8 W9 W10	275 10.8	1682 66.2	790 31.1	5126 201.8	2.8	2400	3140	2480	2290	2190	2090	1900
								41	5290	6920	5460	5040	4820	4600	4190
								3.6	2780	3630	2870	2650	2540	2420	2200
								52	6120	8000	6320	5840	5590	5330	4850
								4	2960	3860	3050	2820	2700	2575	2340
58	6520	8500	6720	6210	5950	5670	5150								