

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
			SW	OD				Static	10	20	30	40	50
			mm/in	mm/in					6	12	19	25	31
710/70R38	172A8/B	DW23B DW25B	715 28.15	1959 77.13	881 34.67	5785 227.8	bar	maximum Load, kg (lbs)					
							psi						
							1.8	11940	7790	6380	5550	5190	5190
							26	26300	17160	14050	12220	11430	11430
							2	12700	8280	6790	5910	5520	5520
							29	27970	18240	14960	13020	12160	12160
							2.2	13430	8760	7180	6250	5840	5840
							32	29580	19300	15810	13770	12860	12860
2.4	14150	9230	6830	6580	6150	6150							
35	31170	20330	15040	14490	13550	13550							