

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
			SW	OD				Static	10	20	30	40	50
			mm/in	mm/in					6	12	19	25	31
600/70R30	158 A8/B	DW18L DW20B	611 24.06	1602 63.07	717 28.25	4681 184.3	bar	maximum Load, kg (lbs)					
							psi						
							1.8	8260	5390	4420	3840	3590	3590
							26	18190	11870	9740	8460	7910	7910
							2	8790	5730	4700	4090	3820	3820
							29	19360	12620	10350	9010	8410	8410
							2.2	9290	6060	4970	4320	4040	4040
							32	20460	13350	10950	9520	8900	8900
2.4	9780	6380	4720	4550	4250	4250							
35	21540	14050	10400	10020	9360	9360							