

# TORQUEMAX AG RADIAL



WITH THE POWER OF CTR\*

## FEATURE

- Stepped lug design

## BENEFIT

- Better Grip

## FEATURE

- Tilted lug tip

## BENEFIT

- Lower vibration at high speeds.

## FEATURE

- Strong & wider lugs

## BENEFIT

- Provides higher contact area leading to higher life

## FEATURE

- Wider tread width

## BENEFIT

- Lower Compaction

## FEATURE

- Lower lug angle at the shoulder

## BENEFIT

- Better traction

## FEATURE

- Rounder shoulder

## BENEFIT

- Lesser soil/crop damage

## FEATURE

- Steel belted radial construction

## BENEFIT

- Protection from Punctures



\*Lower Compaction, Higher Traction and Better Roadability

# LIST OF SIZES

SIZE	L/SI
IF 520/85 R38	167 D
IF 600/70 R30	165 D
IF 600/70 R34	160 D
IF 600/70 R34	167 D
IF 650/60 R34	159 D
IF 710/70 R38	178 D
IF 710/70 R42	179 D
IF 710/75 R42	176 D
VF 520/85 R38	170 D
VF 520/85 R42	174 D/ 177 A8
VF 600/70 R30	170 D
VF 600/70 R30 SB*	170 D
VF 710/70 R42	185 D
VF 710/70 R42 SB*	185 D
VF 710/75 R42	184 D
VF 710/75 R42 SB*	184 D

\* SB - Steel belted

All tyres conform to ETRTO & TRA standards. Sizes available as of 09/2021.

