

FARMAX HPT



FEATURE

- Tilted lug tip

BENEFIT

- Reduced vibration

FEATURE

- Increased lug width

BENEFIT

- Provides longer service life

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Wide tread width

BENEFIT

- Lower Compaction


FEATURE

- Rounder shoulder

BENEFIT

- Reduced soil disturbance

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm/in	mm/in					Tractor application					
		mm/in	mm/in					speed symbol	bar psi	Field Operation	10	30	40
480/80R50	DW15L	485	2038	950	6082	165D/168A8	0.8	5270	3440	2630	2510	2400	2290
							12	11610	7580	5790	5530	5290	5040
	DW16L	19.1	80.2	37.4	239.5	1.2	6670	4350	3340	3180	3050	2900	
						17	14690	9580	7360	7000	6720	6390	
	1.6	7890	5150	3940	3760	3600	3430						
	23	17380	11340	8680	8280	7930	7560						
	1.8	8460	5520	4230	4030	3860	3680						
	26	18630	12160	9320	8880	8500	8110						
	2	8990	5870	4500	4280	4110	3910						
	29	19800	12930	9910	9430	9050	8610						
	3.2	11850	7730	5920	5640	5410	5150						
	46	26100	17030	13040	12420	11920	11340						

All tires confirms ETRTO T&RA & STRO standards