

# TORQUEMAX

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lesser vibration and noise

**FEATURE**

- Mud breaker

**BENEFIT**

- Better self cleaning

**FEATURE**

- Higher angle and lug overlap at centre

**BENEFIT**

- Better roadability



**FEATURE**

- R1-W tread depth

**BENEFIT**

- Longer tyre life

**FEATURE**

- Lower angle at shoulder

**BENEFIT**

- Superior traction

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Lesser damage to soil and crop


**FEATURES**

- Wider tread
- Larger inner volume

**BENEFIT**

- Reduced soil compaction

## MACHINERY



Tractor

\*Lower Compaction, Higher Traction and Better Roadability

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Stars Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm / in	mm / in					Tractor application						
								Speed Symbol	bar psi	Filed Operation	10	20	30	40
650/80R38	DW23B, DW21B, DW20B	675 26.6	2071 81.5	947 37	6181 243	170D/173A8	0.8	3930	5130	4210	3930	3740	3590	3420
							12	8660	11300	9270	8660	8240	7910	7530
							1.2	4980	6500	5330	4980	4740	4550	4330
							17	10970	14320	11740	10970	10440	10020	9540
							1.6	5890	7680	6300	5890	5610	5380	5120
							23	12970	16920	13880	12970	12360	11850	11280
							1.8	6300	8220	6740	6300	6000	5750	5480
							26	13880	18110	14850	13880	13220	12670	12070
							2.1	6900	9000	7750	6900	6570	6300	6000
30	15200	19820	17070	15200	14470	13880	13220							

All tires confirms ETRTO T&RA & STRO standards