RPG

TORQUEMAX

CEAT SPECIALTY

FEATURE
- Tilted lug tip

BENEFIT
- Lesser vibration and noise

FEATURE
- Mud breaker

BENEFIT
- Better self cleaning

FEATURE
- Higher angle and lug overlap at centre

BENEFIT
- Better roadability

FEATURE
- R1-W tread depth

BENEFIT
- Longer tyre life

FEATURE
- Lower angle at shoulder

BENEFIT
- Superior traction

FEATURE
- Rounded shoulder

BENEFIT
- Lesser damage to soil and crop

FEATURES
- Wider tread
- Larger inner volume

BENEFIT
- Reduced soil compaction

*Lower Compaction, Higher Traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum-ference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)						
		SW	OD					MIXED APPLICATION					CYCLIC*	
		mm/in	mm/in	mm/in	mm/in	speed	bar	10	20	30	40 to 65	70	15	30
						symbol	psi	6	12	19	25 to 40	43	9	19
710 70R38	23B DW25B	720 28.3	1959 77.1	850 33.5	5800 228.3	178D	0.8	5000	4260	4100	3940	3590	4530	4310
							12	11010	9380	9030	8680	7910	9980	9490
							1.2	6350	5400	5200	5000	4550	5750	5480
							17	13990	11890	11450	11010	10020	12670	12070
							1.6	7520	6390	6160	5920	5390	6810	6480
							23	16560	14070	13570	13040	11870	15000	14270
							2.0	8560	7280	7010	6740	6130	7750	7380
							29	18850	16040	15440	14850	13500	17070	16260
							2.2	9060	7700	7420	7130	6490	8200	7810
							32	19960	16960	16340	15700	14300	18060	17200
							2.4	9530	8100	7800	7500	6830	8630	8210
							35	20990	17840	17180	16520	15040	19010	18080

All tires confirms ETRTO T&RA & STRO standards