

FARMAX R85

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)																																														
				SW	OD				Speed, km/h (mph)																																														
				mm/in	mm/in				Static	10	20	30	40	50	65																																								
520/85R42	169D / 172A8	TL	DW16L DW18L	530	1951	889 35.0	5791 228.0	bar	6510	4250	3480	3250	3100	2970	2830																																								
				psi	14340			9360								7670	7160	6230	6540	6230																																			
				1																	9780	6380	5230	4890	4650	4460	4250																												
				2																								21540	14050	11520	10770	9360	9820	9360																					
				2.8																															11910	7770	6370	5960	5670	5440	5180														
				41																																						26230	17110	14030	13130	11410	11980	11410							
				3.4																																													13340	8700	7130	6670	6350	6090	5800
				49																																																			
40																																																							