

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
										25	40	50	65	bar	10	15
				mm/in	mm/in					mm/in	mm/in	psi	6	9		
320/65R16	117 D	TL	W10 W9 W11	319	822	374	2453	0.8	360	370	340	330	310	1.0	530	480
								12	790	810	750	730	680	14.5	1170	1060
								1.2	990	1020	940	900	860	1.5	1460	1330
								1.7	2180	2250	2070	1980	1890	21.8	3220	2930
								1.4	1080	1110	1030	990	940	1.8	1600	1460
								20	2380	2440	2270	2180	2070	25.4	3520	3220
								2.0	1330	1370	1270	1220	1160	2.5	1970	1800
								2.9	2930	3020	2800	2690	2560	36.3	4340	3960
								2.4	1480	1520	1410	1350	1285	3.0	2180	1990
								35	3260	3350	3110	2970	2830	43.5	4800	4380

All tires confirms ETRTO T&RA & STRO standards