

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
				mm/in	mm/in					16	25	31	40	psi	6	9
340/65R18	122 D	TL	W11 W10 W12	343	899	410	2669	0.8	200	200	190	180	170	1.0	290	260
								12	440	440	420	400	370	14.5	640	570
								1.2	240	250	230	220	210	1.5	360	330
								1.7	530	550	510	480	460	21.8	790	730
								1.4	590	600	560	540	510	1.8	870	790
								20	1300	1320	1230	1190	1120	25.4	1920	1740
								1.8	1460	1500	1390	1330	1270	2.3	2160	1970
								26	3220	3300	3060	2930	2800	32.6	4760	4340
								2.0	1550	1600	1480	1420	1350	2.5	2300	2090
								29	3410	3520	3260	3130	2970	36.3	5070	4600
								2.2	1640	1690	1570	1500	1430	2.8	2430	2220
								32	3610	3720	3460	3300	3150	39.9	5350	4890
								2.4	1730	1780	1640	1580	1500	3.0	2550	2330
								35	3810	3920	3610	3480	3300	43.5	5620	5130

All tires confirms ETRTO T&RA & STRO standards