RPG

TORQUEMAX

CEAT SPECIALTY

FEATURE
- Stepped lug design

BENEFIT
- Better Grip

FEATURE
- Tilted lug tip

BENEFIT
- Lower vibration at high speeds.

FEATURE
- Strong & wider lugs

BENEFIT
- Provides higher contact area leading to higher life

FEATURE
- Wider tread width

BENEFIT
- Lower Compaction

FEATURE
- Lower lug angle at the shoulder

BENEFIT
- Better traction

FEATURE
- Rounder shoulder

BENEFIT
- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum-ference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)						
		SW	OD					MIXED APPLICATION					CYCLIC*	
		mm/in	mm/in	mm/in	mm/in	speed	bar	10	20	30	40 to 65	70	15	30
						symbol	psi	6	12	19	25 to 40	43	9	19
IF710/ 75R42	DW25B DW23B DW24B	715 28.1	2133 84.0	944 37.2	6306 248.3	176D	0.8	6010	5110	4920	4730	4300	7330	6150
							12	13240	11260	10840	10420	9470	16150	1355
							1	6850	5820	5610	5390	4900	8350	7010
							15	15090	12820	12360	11870	10790	18390	15440
							1.2	7620	6480	6240	6000	5460	9300	7800
							17	16780	14270	13740	13220	12030	20480	17180
							1.4	8340	7100	6830	6570	5980	10180	8540
							20	18370	15640	15040	14470	13170	22420	18810
							1.6	9020	7670	7380	7100	6830	11010	9230
							23	20990	17840	17180	16520	15040	24250	20330

All tires confirms ETRTO T&RA & STRO standards