RPG

TORQUEMAX

CEAT SPECIALTY

FEATURE
- Stepped lug design

BENEFIT
- Better Grip

FEATURE
- Tilted lug tip

BENEFIT
- Lower vibration at high speeds.

FEATURE
- Strong & wider lugs

BENEFIT
- Provides higher contact area leading to higher life

FEATURE
- Wider tread width

BENEFIT
- Lower Compaction

FEATURE
- Lower lug angle at the shoulder

BENEFIT
- Better traction

FEATURE
- Rounder shoulder

BENEFIT
- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum-ference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
		SW	OD					MIXED APPLICATION			CYCLIC*
		mm/in	mm/in	mm/in	mm/in	speed symbol	bar psi	static	Up to 65km/h Up to 40mph	70 43	10 6
VF 600/ 70R30	DW20L, DW21L	603 23.7	1602 63.1	692 27.3	4731 186.3	170D	0.8	7270	3160	2880	4420
							12	16010	6960	6340	9740
							1.2	9200	4000	3640	5600
							17	20260	8810	8020	12330
							1.6	10880	4730	4300	6620
							23	23960	10420	9470	14580
							2	12400	5390	4900	7550
							29	27310	11870	10790	16630
							2.4	13800	6000	5460	8400
							35	30400	13220	12030	18500

All tires confirms ETRTO T&RA & STRO standards