

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



High Powered Tractor

Size	Rim	Type	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
			SW	OD					MIXED APPLICATION			CYCLIC*
			mm/in	mm/in					static	Up to 65km/h Up to 40mph	70 43	10 6
VF 800/ 70R38 SB*	DW 27B DW 28B DW 30B	TL	810	2085	898	6124	187D	0.8	11800	5130	4670	7180
			28.3	77.1	33.5	228.3		12	25990	11300	10290	15810
								1.2	14950	6500	5920	9100
								17	32930	14320	13040	20040
								1.6	17690	7690	7000	10770
								23	38960	16940	15420	23770
								2	20150	8760	7970	12260
								29	44380	19300	17560	27000
								2.4	22430	9750	8870	13650
				35	49410	21480	19540	30070				

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards