

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



High Powered Tractor

Size	Rim	Type	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
			SW	OD					MIXED APPLICATION			CYCLIC*
			mm/in	mm/in					static	Up to 65km/h Up to 40mph	70 43	10 6
VF 650/ 65R34*SB	DW23B DW21B	TL	650	1710	750 29.5	5061 199.2	167D	0.8	8370	3640	3310	5100
			12	18440				8020	7290	11230		
			1.2	10600				4610	4200	6450		
			17	23350				10150	9250	14210		
			1.4	11590				5040	4590	7060		
			20	25530				11100	10110	15550		
			1.6	12540				5450	4960	7630		
			23	27620				12000	10930	16810		

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards