

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life

FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm/in	mm/in					Tractor application					
								Static	10 6	30 19	40 25	50 31	65 40
710/ 50R26.5 FT *SB	AG 24.00	710 28	1383 54.4	621 24.4	4188 164.9	170D 170D	0.8	5360	4190	3520	3170	2820	2330
							12	11810	9230	7750	6980	6210	5130
							1.6	8070	6320	5300	4770	4250	3510
							23	17780	13920	11670	10510	9360	7730
							2.4	10240	8010	6720	6050	5380	4450
							35	22560	17640	14800	13330	11850	9800
							3.2	12120	9490	7960	7170	6380	5270
							46	26700	20900	17530	15790	14050	11610
							4	13800	10800	9060	8160	7260	6000
58	30400	23790	19960	17970	15990	13220							

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards