

FLOATMAX RT

FEATURE
Directional Lug

BENEFIT
Higher traction,
Comfortable ride

FEATURE
Robust Centre Blocks

BENEFIT
Low noise and smooth
run on hard surface

FEATURE
Steel belted radial
construction

BENEFIT
Protection from
Punctures



FEATURE
Rounded Shoulder

BENEFIT
Less damage to
soil & crops


FEATURE
Interconnected
grooves

BENEFIT
Better self cleaning
properties

FEATURE
Flatter Crown width

BENEFIT
Larger footprint,
lower compaction

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)					
		SW	OD	Radius				Speed, km/h (mph)					
		mm	mm	mm	mm	Speed	bar	MIXED APPLICATION					
		in	in	in	in	Symbol	psi	Static	10	30	40	50	65
								6	19	25	31	40	
385/65 R 22.5 RT SB*	AG11.75	389	1072	491	3183	164D	4	7180	5620	4710	4240	3780	3120
							58	15810	12380	10370	9340	8330	6870
							5	8170	6390	5360	4830	4300	3550
		15.3	42.2	19.3	125.3	164D	73	18000	14070	11810	10640	9470	7820
							6	9090	7110	5960	5370	4780	3950
							87	20020	15660	13130	11830	10530	8700
							8	10740	8410	7050	6350	5650	4670
							116	23660	18520	15530	13990	12440	10290
							9	11500	9000	7550	6800	6050	5000
					131	25330	19820	16630	14980	13330	11010		

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards