

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
										16	25	31	40	psi	6	9
540/ 65R28	142D	TL	W16L W18L	550 21.7	1416 55.7	642 25.3	4186 164.8	0.8	2040	2100	1940	1860	1770	1	3010	2740
								12	4490	4630	4270	4100	3900	15	6630	6040
								1.0	2320	2390	2210	2120	2020	1.25	3430	3130
								15	5110	5260	4870	4670	4450	18	7560	6890
								1.3	2700	2780	2570	2470	2350	1.625	4000	3640
								19	5950	6120	5660	5440	5180	24	8810	8020
								1.6	3050	3140	2900	2780	2650	2	4510	4110
								23	6720	6920	6390	6120	5840	29	9930	9050

All tires confirms ETRTO T&RA & STRO standards