

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
										16	25	31	40	psi	6	9
650/ 65R42	165D	TL	DW20BL W18L	645	1939	896	5854	0.8	3250	3350	3100	2970	2830	1	4810	4390
								12	7160	7380	6830	6540	6230	15	10590	9670
								1.2	4130	4250	3930	3770	3590	2	6100	5560
								17	9100	9360	8660	8300	7910	22	13440	12250
								1.5	4700	4850	4480	4290	4090	2	6950	6340
								22	10350	10680	9870	9450	9010	27	15310	13960
								2.0	5570	5740	5300	5080	4840	3	8230	7500
								29	12270	12640	11670	11190	10660	36	18130	16520
								2.4	5920	6100	5640	5410	5150	3	8760	7980
								35	13040	13440	12420	11920	11340	44	19300	17580

All tires confirms ETRTO T&RA & STRO standards