

FARMAX R75

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Speed, km/h (mph)					
				SW	OD				Static	10	20	30	40	50
				mm/in	mm/in					6	12	19	25	31
400/ 75R38	138 A8/B	TL	W12 W13 W14	404	1565	723	4646	0.8	3610	2360	1930	1680	1570	1570
								12	7950	5200	4250	3700	3460	3460
								1	4120	2690	2200	1920	1790	1790
								15	9070	5930	4850	4230	3940	3940
								1.4	5010	3270	2680	2330	2180	2180
								20	11040	7200	5900	5130	4800	4800
								1.6	5430	3540	2900	2530	2360	2360
								23	11960	7800	6390	5570	5200	5200