

TORQUEMAX

FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life



FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF650/ 60R34	DW23B	650 25.6	1644 64.7	725 28.5	4865 191.5	168D		0.8	7520	3500	3270	3270	2980	1.6	4580
								12	16560	7710	7200	7200	6560	23	10090
								1.2	9550	4450	4150	4150	3780	2	5810
								17	21040	9800	9140	9140	8330	29	12800
								1.6	11290	5260	4910	4910	4470	2.4	6870
								23	24870	11590	10810	10810	9850	35	15130
								2	12880	6000	5600	5600	5100	2.8	7840
								29	28370	13220	12330	12330	11230	41	17270

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards