

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION				CYCLIC*			
		mm/in	mm/in					static	10	20	25 to 65	70	bar	30	
VF650/ 65R34	DW23B DW21B	650 25.6	1710 67.3	750 29.5	5061 199.2	167D	0.8	8370	3900	3640	3640	3310	1.6	5100	
							12	18440	8590	8020	8020	7290	23	11230	
							1.2	10600	4940	4610	4610	4200	2	6450	
							17	23350	10880	10150	10150	9250	29	14210	
							1.4	11590	5400	5040	5040	4590	2.2	7060	
							20	25530	11890	11100	11100	10110	32	15550	
							1.6	12540	5840	5450	5450	4960	2.4	7630	
							23	27620	12860	12000	12000	10930	35	16810	

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards