

FARMAX HPT



FEATURE

Lug Tip Step

BENEFIT

Increase the grip and reducing the tractor slip

FEATURE

Lug base tie bar

BENEFIT

Additional support to lugs and also helps to remove mud from lugs

FEATURE

Extra wide tread

BENEFIT

Wider footprint provides increased stability

FEATURE

50° lug angle at centre

BENEFIT

Smoother road driving comfort, less noise and vibration

FEATURE

Rounder shoulder

BENEFIT

Provides less soil damage
Better Grip


FEATURE

Deeper Tread Depths

BENEFIT

Provides improved traction and gripping power longer tire life

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
								Tractor application						
		mm/in	mm/in					Static	10	20	30	40	50	65
710/70R42	DW23B	28.2	81.1	36.7	6151	176D/179A8	0.8	7870	5130	4210	3930	3740	3590	3420
							12	17330	11300	9270	8660	8240	7910	7530
	1.2						9980	6510	5340	4990	4750	4560	4340	
	17						21980	14340	11760	10990	10460	10040	9560	
	1.6						11800	7700	6310	5900	5620	5390	5130	
	23						25990	16960	13900	13000	12380	11870	11300	
	2.0						13430	8760	7180	6720	6390	6130	5840	
	29						29580	19300	15810	14800	14070	13500	12860	
	2.4						14950	9750	8400	7480	7120	6830	6500	
	35						32930	21480	18500	16480	15680	15040	14320	
	2.8						16330	10650	8730	8170	7770	7460	7100	
41	35970	23460	19230	18000	17110	16430	15640							

All tires confirms ETRTO T&RA & STRO standards