

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)						
				SW	OD				Speed, km/h (mph)						
				mm/in	mm/in				mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in
520/85R42	169D/172A8	TL	DW16L DW18L	530 20.9	1951 76.8	889 35.0	5791 228.0	bar							
								psi	Static	10	20	30	40	50	65
									6	12	19	25	31	40	
								0.8	5700	3720	3050	2850	2720	2600	2480
								12	12560	8190	6720	6280	5460	5730	5460
								1	6510	4250	3480	3250	3100	2970	2830
								15	14340	9360	7670	7160	6230	6540	6230
								2	9780	6380	5230	4890	4650	4460	4250
								29	21540	14050	11520	10770	9360	9820	9360
								2.8	11910	7770	6370	5960	5670	5440	5180
41	26230	17110	14030	13130	11410	11980	11410								
3.4	13340	8700	7130	6670	6350	6090	5800								
49	29380	19160	15700	14690	13990	13410	12780								

All tires confirms ETRTO T&RA & STRO standards