

# FARMAX R65

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity

**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance


**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
										16	25	31	40	psi	6	9
650/ 65R38	163D	TL	DW20B	645 25.4	1811 71.3	821 32.3	5490 216.2	0.8	3160	3260	3010	2890	2750	1.0	4680	4260
								23	10440	10770	9960	9540	9090	29	15440	14070
								1.2	3740	3850	3560	3410	3250	1.5	5530	5040
								12	6960	7180	6630	6370	6060	15	10310	9380
								1.5	4260	4380	4050	3890	3700	1.9	6290	5740
								22	9380	9650	8920	8570	8150	27	13850	12640
								2.0	5040	5190	4800	4600	4380	2.5	7450	6790
								29	11100	11430	10570	10130	9650	36	16410	14960
								2.4	5610	5780	5340	5120	4875	3	8290	7560
								35	12360	12730	11760	11280	10740	44	18260	16650

All tires confirms ETRTO T&RA & STRO standards