

# LOADPRO



**FEATURE**

Greater lug overlap and more lugs in footprint

**BENEFIT**

Uniform load distribution

**FEATURE**

Extra reinforced Sidewalls

**BENEFIT**

Additional lateral stability


**FEATURE**

Strong bead

**BENEFIT**

Better carcass strength and load carrying capacity

## MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Recommend load, kg (lbs)							
		SW	OD	Radius	mm	Speed		Constant load					Cyclic operation		
		mm	mm	mm	mm	bar		10	20	30	40	50	10	15	
		in	in	in	in	psi		6	12	19	25	31	6	9	
280/ 80R20	W9	282	956	430	2823	133 A8/B	1.6	2760	1500	1310	1250	1200	1200	1800	1610
							23	6080	3300	2890	2750	2640	2640	3960	3550
	W10						2.0	3150	1710	1490	1420	1370	1370	2060	1840
							29	6940	3770	3280	3130	3020	3020	4540	4050
	3.0						4000	2180	1900	1810	1740	1740	2610	2330	
	44						8810	4800	4190	3990	3830	3830	5750	5130	
	4						4740	2580	2250	2140	2060	2060	3090	2760	
	58						10440	5680	4960	4710	4540	4540	6810	6080	