

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Speed	Recommend load, kg (lbs)							
		SW	OD	Radius	mm	mm			bar	Constant load					Cyclic operation	
		mm	mm	mm	mm	mm			psi	10	20	30	40	50	10	15
		in	in	in	in	in			Symbol	6	12	19	25	31	6	9
405/ 70R24	W13L	404	1170	527	3529	152 A8/B	1.6	4780	2600	2270	2160	2080	2080	3120	2790	
							23	10530	5730	5000	4760	4580	4580	6870	6150	
							2.2	5770	3140	2740	2610	2510	2510	3770	3360	
	W12D						32	12710	6920	6040	5750	5530	5530	8300	7400	
							W14L	3.2	7180	3900	3400	3240	3120	3120	4680	4180
								46	15810	8590	7490	7140	6870	6870	10310	9210
	4						8170	4440	3870	3690	3550	3550	5330	4760		
	58						18000	9780	8520	8130	7820	7820	11740	10480		