

ROW CROP AG RADIAL

WITH THE POWER OF CTR* 300/95 R 46 FARMAX RC 143D/146A8



MACHINERY

2WD Tractor 4WD Tractor MFWA (Mechanical front wheel assist) Self propelled sprayer & towed sprayer





TECHNICAL SPECIFICATION

SIZE	300/95R46 (12.4R46)
PATTERN	FARMAX RC
TREAD DESIGN	TRACTOR R1
TT/TL	TL

Size	Rim	Unloaded dimension		Loaded Static	Rolling Circum	PR,Stars Load	Infl. Press	Recommend load, kg (lbs)						
		SW	OD	Radius		Index		Speed, km/h (mph)						
		mm / in	mm / in	mm / in	mm / in	Speed	bar	field	10	25	40	50	65	70
						Symbol	psi							
300/95R46 (12.4 R 46)	W9 , W10	300 11.8	1738 68.4	817 32.1	5155 203	143D/ 146A8	2.4	2470	3230	2550	2370	2260	2150	1960
							35	5440	7110	5620	5220	4980	4740	4320
							2.8	2700	3530	2780	2590	2470	2350	2140
							41	5950	7780	6120	5700	5440	5180	4710
							3.2	2920	3810	3010	2790	2670	2540	2310
							46	6430	8390	6630	6150	5880	5590	5090
							3.6	3130	4090	3230	3000	2860	2725	2480
							52	6890	9010	7110	6610	6300	6000	5460

All tires confirms ETRTO T&RA & STRO standards





CEAT Limited Is One Of The Leading Manufacturers Established In 1958 CEAT Is A Part Of RPG Enterprises, Among The Top 5 Business Houses In India With A Group Turn Over Of USD 2.5billion. CEAT 57 Years Of Experience, CEAT serves customers in 102 countries across 5 plants and wide range of tires in all segments like Truck Bus Bias and Radial, SUV, Passengers, 2&3 Wheelers, Floatation, Mining, Earthmover, Farm and Other Special Application off the Road Tires.