


85/80/70 SERIES AG RADIAL

WITH THE POWER OF CTR* 420/70R30 FARMAX R70



MACHINERY

2WD Tractor 4WD Tractor MFWA (Mechanical front wheel assist)





TECHNICAL SPECIFICATION

SIZE	420/70R30
PATTERN	FARMAX R70
TREAD DESIGN	TRACTOR R1W
TT/TL	TL

			tire nsion	Static Loaded	Rolling circm.	Load	Infl.	Recommended load, kg (lbs)					
		uiiile	IISIUII	Loaded	CITCIII.	Loau	11111.	Speed, km/h (mph)					
Size	Rim	SW	OD	radius		Index	press.						
		mm	mm	mm	mm	Speed	bar	Static	10	20	30	40	50
		in	in	in	in	Symbol	psi	Static	6	12	19	25	31
							0.8	3240	2120	1730	1510	1410	1410
420/70R30	W12						12	7140	4670	3810	3330	3110	3110
	W13	430	1398	639	4156		1.0	3700	2420	1980	1720	1610	1610
	W14L	16.9	55.0	25.1	163.6		15	8150	5330	4360	3790	3550	3550
							1.3	4320	2820	2310	2010	1880	1880
							19	9520	6210	5090	4430	4140	4140
						134 A8	1.6	4880	3180	2610	2270	2120	2120
						134 B	23	10750	7000	5750	5000	4670	4670

All tires confirms ETRTO T&RA & STRO standards





CEAT Limited Is One Of The Leading Manufacturers Established In 1958 CEAT Is A Part Of RPG Enterprises, Among The Top 5 Business Houses In India With A Group Turn Over Of USD 2.5billion. CEAT 57 Years Of Experience, CEAT serves customers in 102 countries across 5 plants and wide range of tires in all segments like Truck Bus Bias and Radial, SUV, Passengers, 2&3 Wheelers, Floatation, Mining, Earthmover, Farm and Other Special Application off the Road Tires.