

ELEVETA



FEATURE

- Specially designed for heavy duty forklift service

BENEFIT

- Excellent durability

FEATURE

- Superior tread compound

BENEFIT

- High resistance to wear, tear & cuts

FEATURE

- Alternate continuous lugs with high contact area

BENEFIT

- Maximum stability and load distribution

FEATURE

- Strong nylon casing

BENEFIT

- High load carrying capacity

MACHINERY



Forklift

Size	LI/SS	Type	PR	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Load capacity											
					SW	OD				Lift Truck				Side loader		Other Vehicle					
										Steering wheel	Load wheel		Speed Km/h/ mph		Static						
					mm	mm				25	35	25	35	10	25	50	15	22	5	15	30
					in	in				in	in	in	in	psi	Recommended Load kg/lbs						
8.25-15	146A5	TT	12	6.5	236	847	386	2515	7	3000	2780	3750	3750	4530	3000	2780	3900	3000	2520		
					9	33	15	99	104	6610	6120	8590	8260	9980	6610	6120	8590	6610	5550		

Also available in sizes: 6.00-9/6.90-9, 6.50-10, 7.00-12, 8.25-15
All tires confirms ETRTO T&RA & STRO standards