

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance

FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLN	nu	IIII. FI635	Static	10	20	30	40	50
									515	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	noodiiiiidha loda kg / lb3					
460/85R30	145 A8/B	F	W16L W15L W14L	480 18.9	1544 60.8	701 27.6	4574 180.1	0.8	4440	2900	2370	2070	1930	1930
								12	9780	6390	5220	4560	4250	4250
								1	5060	3300	2710	2350	2200	2200
								15	11150	7270	5970	5180	4850	4850
								1.3	5910	3860	3160	2750	2570	2570
								19	13020	8500	6960	6060	5660	5660
								1.6	6670	4350	3570	3100	2900	2900
								23	14690	9580	7860	6830	6390	6390

All tires confirms ETRTO T&RA & STRO standards